



VULCAN

INFRA-RED EMITTERS APPLICATIONS CERAMICS INDUSTRY

Litho Pre-Heat

The Vulcatherm V6 500 watt emitter is cheaper to run because it is half the wattage of the original heater. The heater's variable temperature controller allows the operator to choose to use between 20% and 100% power. In addition, the E27 screw-in connection enables the emitter to be easily maintained or replaced.



So far the company has installed 140 Vulcan heaters in the hotelware plant, for use with both china holloware and flat ware such as plates. An additional 60 units have been supplied to the main Barlaston plant for heating china holloware. Eventually the company plans to introduce the new heaters for drying holloware at all of its operating plants, says Mr Belcher.

DISCLAIMER

Any advice, opinion, recommendation or information is given to assist the use of the company's products but on the basis that the end user must ensure their suitability for the application intended.

In particular the company cannot accept liability for loss or damage which may arise from the incorrect use of its products or from poor workmanship on the part of the user.

Information is compiled from routine quality control testing and does not constitute a specification.

Information is provided in good faith and is subject to review whenever necessary and no guarantee or warranty is implied.

THIS CD-ROM IS VALID UNTIL 31/12/2002 TO RECEIVE A CURRENT ISSUE PLEASE CONTACT VULCAN REFRACTORIES

Vulcan Refractories Limited

Tel. +44 (0)1538 752 238 Fax. +44 (0) 1538 753 349 E-Mail enquiries@vulcanrefractories.com Web www.vulcanrefractories.com